

MS.k

Metering dosing pumps

Constant flow rate regulation.
PVDF pump head with FPM seals



- LCD 2.1/2 digit display
- Flow rate digital adjustment 0-100% by keys
- PVDF pump head as standard
- Power on led
- Led Alarm
- Solenoid pulse Led
- Chemical dosing alarm level as standard
- Start/Stop key
- Plastic box IP65 protection degree
- Percentage by UP/DOWN arrow keys
- Start/pause dosing

SELECTION GUIDE

MODEL	FLOW RATE MAX (l/h)	PRESSURE MAX (bar)	FREQUENCY MAX (imp/min)	ML/PULSE	MAX SUCTION HIGH (m)	STANDARD POWER SUPPLY (*)	WEIGHT (kg)
MSK 01-15	1	15	120	0,14	2.0	230 V-50/60 Hz	2,3
MSK 02-10	2	10	120	0,28	2.0	230 V-50/60 Hz	2,3
MSK 05-07	5	7	120	0,69	2.0	230 V-50/60 Hz	2,3
MSK 10-10	10	10	180	0,93	2.0	230 V-50/60 Hz	2,3
MSK 20-03	20	3	200	1,67	2.0	230 V-50/60 Hz	2,3
MSK 50-01	50	1	220	3,97	2.0	230 V-50/60 Hz	2,3

(*) For other power supply consult factory.

MATERIALS OF CONSTRUCTION

PARTS	MATERIALS
Pump head	PVDF
Diaphragm	PTFE
Connections	PVDF
Foot filter	Polypropylene
Injection valve	Polypropylene
Suction tube	PVC crystal 4x6 mm. (8x12 mm. - MS.K 50-01)
Delivery tube	Polyethylene 4x6 mm. (8x12 mm. - MS.K 50-01)
Standard valves	Ceramic ball
Seals	FPM (on request: EPDM)
On request	Level connection
Max current	1A

OVERALL DIMENSIONS

